

TQMHシリーズ電気特性表

基板数	全長 (mm)	100V		200V		希望小売価格		電源型番	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	コード		要信号線	信号線不要
1	65	0.9	2.8	1.0	5.1	¥16,000			
2	115	1.2	3.1	1.2	5.8				
3	165	1.5	3.4	1.5	6.4				
4	215	1.8	3.7	1.8	7.1				
5	265	2.2	4.0	2.1	7.7				
6	315	2.5	4.3	2.4	8.4				
7	365	2.8	4.6	2.7	9.0				
8	415	3.1	4.9	3.0	9.7				
9	465	3.4	5.2	3.2	10.3				
10	515	3.7	5.5	3.5	11.0				
11	565	4.0	5.8	3.8	11.6				
12	615	4.3	6.1	4.1	12.3				
13	665	4.6	6.4	4.4	12.9				
14	715	5.0	6.7	4.7	13.6				
15	765	5.3	7.0	5.0	13.9				
16	815	5.7	7.3	5.3	14.1				
17	865	6.0	7.7	5.7	14.2				
18	915	6.4	8.4	6.1	14.7				
19	965	6.8	8.7	6.5	15.3				
20	1,015	7.1	9.1	7.0	15.8	¥32,000			
21	1,065	7.5	9.4	7.4	16.5				
22	1,115	7.9	9.7	7.8	16.7				
23	1,165	8.2	10.1	8.1	17.2				
24	1,215	8.5	10.4	8.5	17.7				
25	1,265	8.9	10.8	8.9	18.2				
26	1,315	9.3	11.1	9.3	18.6				
27	1,365	9.6	11.5	9.7	19.0				
28	1,415	10.0	11.8	10.0	19.1				
29	1,465	10.3	12.1	10.4	19.2				
30	1,515	10.6	12.5	10.7	19.6				
31	1,565	11.0	12.9	11.1	19.9				
32	1,615	11.4	13.2	11.5	20.2				
33	1,665	11.7	13.6	11.8	20.7				
34	1,715	12.2	14.0	12.2	21.1				
35	1,765	12.5	14.3	12.6	21.3				
36	1,815	12.8	14.6	13.0	21.6				
37	1,865	13.1	15.0	13.3	21.9				
38	1,915	13.5	15.6	13.7	22.3				
39	1,965	13.8	15.9	14.0	22.6	¥48,000			
40	2,015	14.2	16.0	14.3	22.7				
41	2,065	14.5	16.4	14.7	22.9				
42	2,115	14.9	16.7	15.1	23.3				
43	2,165	15.3	17.1	15.5	23.6				
44	2,215	15.6	17.4	15.8	24.0				
45	2,265	15.9	17.7	16.2	24.3				
46	2,315	16.2	18.0	16.5	24.4				
47	2,365	16.6	18.3	16.8	24.8				
48	2,415	16.8	18.6	17.1	25.2				
49	2,465	17.1	18.9	17.4	25.4				
50	2,515	17.5	19.3	17.8	25.7				
51	2,565	17.8	19.6	18.1	26.0				
52	2,615	18.1	19.8	18.4	26.3				
53	2,665	18.4	20.2	18.7	26.5				
54	2,715	18.8	20.5	19.0	26.8				
55	2,765	19.1	20.9	19.4	27.1				
56	2,815	19.5	21.3	19.7	27.4				
57	2,865	19.8	21.6	20.1	27.7	¥64,000			
58	2,915	20.2	22.0	20.4	28.0				
59	2,965	20.6	22.3	20.8	28.4				
60	3,015	20.9	22.7	21.2	28.7				
61	3,065	21.3	23.0	21.5	29.0				
62	3,115	21.6	23.4	21.8	29.3				
63	3,165	21.9	23.5	22.2	29.6				
64	3,215	22.1	23.8	22.3	29.7				
65	3,265	22.4	24.1	22.6	29.9				
66	3,315	22.7	24.5	22.9	30.2				
67	3,365	23.0	24.9	23.2	30.5				
68	3,415	23.5	25.2	23.6	30.8				
69	3,465	23.8	25.6	24.0	31.1				
70	3,515	24.2	25.9	24.3	31.4				
71	3,565	24.5	26.3	24.7	31.8				
72	3,615	24.8	26.6	25.0	32.0				
73	3,665	25.2	26.9	25.4	32.3				
74	3,715	25.6	27.3	25.7	32.6				
75	3,765	25.9	27.4	26.0	32.9				

基板数	全長 (mm)	100V		200V		希望小売価格	電源型番	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	コード	要信号線	信号線不要
76	3,815	26.0	27.8	26.2	33.1	¥64,000	TB-24V-060A	TC-24V-060
77	3,865	26.4	28.1	26.5	33.3			
78	3,915	26.7	28.5	26.8	33.6			
79	3,965	27.1	28.8	27.2	34.0			
80	4,015	27.5	29.2	27.6	34.2			
81	4,065	27.8	29.6	27.9	34.5			
82	4,115	28.2	29.9	28.2	34.8			
83	4,165	28.6	30.4	28.7	35.1			
84	4,215	29.1	30.9	29.1	35.6			
85	4,265	29.5	31.2	29.5	35.9			
86	4,315	29.9	31.5	29.9	36.3			
87	4,365	30.2	31.7	30.2	36.5			
88	4,415	30.4	31.9	30.5	36.7			
89	4,465	30.5	32.2	30.6	36.8			
90	4,515	30.8	32.5	30.8	37.0			
91	4,565	31.2	32.9	31.1	37.4			
92	4,615	31.5	33.1	31.4	37.7			
93	4,665	31.8	33.2	31.6	37.9			
94	4,715	32.0	33.5	31.8	38.1			
95	4,765	32.3	33.9	32.1	38.3			
96	4,815	32.6	34.2	32.5	38.6			
97	4,865	32.9	34.6	32.9	38.9			
98	4,915	33.3	34.9	33.2	39.2			
99	4,965	33.6	35.2	33.5	39.5			
100	5,015	33.8	35.5	33.8	39.8			
101	5,065	34.1	35.8	34.1	40.1			
102	5,115	34.5	36.2	34.4	40.3			
103	5,165	34.8	36.5	34.8	40.7			
104	5,215	35.2	36.9	35.1	41.0			
105	5,265	35.6	37.3	35.4	41.3			
106	5,315	36.0	37.7	35.9	41.7			
107	5,365	36.4	38.1	36.3	42.1			
108	5,415	36.8	38.4	36.7	42.4			
109	5,465	37.1	38.8	37.0	42.7			
110	5,515	37.5	39.1	37.3	43.1			
111	5,565	37.8	39.4	37.7	43.4			
112	5,615	38.1	39.7	37.9	43.6			
113	5,665	38.3	40.0	38.2	43.9			
114	5,715	38.6	40.3	38.4	44.0			
115	5,765	38.9	40.5	38.5	44.2			
116	5,815	39.2	40.8	38.8	44.4			
117	5,865	39.5	41.1	39.3	44.8			
118	5,915	39.8	41.4	39.5	45.0			
119	5,965	40.1	41.7	39.7	45.3			
120	6,015	40.4	42.0	40.1	45.6			
121	6,065	40.7	42.3	40.5	46.0			
122	6,115	41.0	42.6	40.8	46.3			
123	6,165	41.3	43.1	41.1	46.6			
124	6,215	41.8	43.5	41.5	46.9			
125	6,265	42.2	43.7	41.9	47.3			
126	6,315	42.4	43.9	42.2	47.6			
127	6,365	42.6	44.3	42.3	47.7			
128	6,415	43.0	44.6	42.7	48.1			
129	6,465	43.3	44.9	43.1	48.5			
130	6,515	43.6	45.3	43.4	48.7			
131	6,565	44.0	45.7	43.7	49.0			
132	6,615	44.3	46.1	43.8	49.1			
133	6,665	44.6	46.4	44.1	49.4			
134	6,715	44.9	46.7	44.3	49.6			
135	6,765	45.2	47.0	44.6	49.9			
136	6,815	45.5	47.3	45.1	50.4			
137	6,865	45.8	47.6	45.5	50.7			
138	6,915	46.2	47.9	45.8	51.0			
139	6,965	46.6	48.2	46.2	51.4			
140	7,015	47.0	48.6	46.6	51.8			
141	7,065	47.3	48.8	46.9	52.1			
142	7,115	47.5	49.0	47.1	52.2			
143	7,165	47.7	49.2	47.3	52.5			
144	7,215	48.0	49.5	47.6	52.7			
145	7,265	48.3	50.0	47.9	53.0			
146	7,315	48.8	50.2	48.3	53.4			
147	7,365	49.0	50.7	48.6	53.7			
148	7,415	49.5	50.9	49.0	54.1			
149	7,465	49.6	51.1	49.2	54.3			
150	7,515	49.8	51.4	49.4	54.5			
						¥128,000	TB-24V-090A	TC-24V-100