

TXDHシリーズ電気特性表

基板数	両側タイプ全長 (mm)	片側タイプ全 長(mm)	100V		200V		希望小売価格		電源型番		マグネット 使用数
			消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	コード	コネクタ	要信号線	信号線不要	
1	53	50	2.3	2.8	2.3	5.8	¥10,200	¥10,700	TB-24V-030A	TC-24V-020	1
2	103	100	3.4	3.8	3.4	6.8					2
3	153	150	4.6	4.9	4.6	7.8					
4	203	200	5.9	6.1	5.9	9.0					
5	253	250	7.0	7.2	7.0	9.8					
6	303	300	8.1	8.3	8.1	10.8					
7	353	350	9.3	9.4	9.2	11.6					
8	403	400	10.5	10.6	10.4	12.6					
9	453	450	11.6	11.7	11.5	13.6					
10	503	500	12.9	12.9	12.7	14.4					
11	553	550	14.0	14.0	13.8	15.6	¥18,800	¥19,300	TB-24V-030A	TC-24V-020	3
12	603	600	15.1	15.0	14.9	16.6					
13	653	650	16.3	16.2	16.1	17.6					
14	703	700	17.5	17.5	17.2	18.6					
15	753	750	18.6	18.7	18.3	19.6					
16	803	800	19.8	19.8	19.4	20.6					
17	853	850	20.9	20.9	20.5	21.6					
18	903	900	22.0	22.0	21.5	22.6					
19	953	950	23.2	23.2	22.8	23.8					
20	1,003	1,000	23.6	23.8	23.3	26.8					
21	1,053	1,050	24.6	24.8	24.3	27.6	¥27,400	¥27,900	TB-24V-060A	TC-24V-060	4
22	1,103	1,100	25.7	25.8	25.3	28.6					
23	1,153	1,150	26.9	27.1	26.6	29.8					
24	1,203	1,200	27.9	28.1	27.5	30.4					
25	1,253	1,250	29.0	29.1	28.5	31.4					
26	1,303	1,300	30.0	30.1	29.6	32.4					
27	1,353	1,350	31.1	31.2	30.7	33.4					
28	1,403	1,400	32.4	32.5	31.7	34.4					
29	1,453	1,450	33.4	33.5	32.9	35.2					
30	1,503	1,500	34.6	34.7	33.9	36.2					
31	1,553	1,550	35.6	35.8	35.0	37.4	¥35,900	¥36,400	TB-24V-060A	TC-24V-060	5
32	1,603	1,600	36.8	36.8	36.1	38.4					
33	1,653	1,650	38.0	38.1	37.4	39.4					
34	1,703	1,700	39.3	39.3	38.5	40.4					
35	1,753	1,750	40.3	40.4	39.6	41.6					
36	1,803	1,800	41.3	41.4	40.6	42.4					
37	1,853	1,850	42.3	42.3	41.6	43.4					
38	1,903	1,900	43.4	43.4	42.6	44.2					
39	1,953	1,950	44.6	44.5	44.0	45.6					
40	2,003	2,000	45.9	46.0	45.1	47.3					
41	2,053	2,050	47.3	47.5	46.3	49.0	¥44,500	¥45,000	TB-24V-090A	TC-24V-100	6
42	2,103	2,100	48.4	48.6	47.4	50.1					
43	2,153	2,150	49.4	49.7	48.5	51.1					
44	2,203	2,200	50.6	50.9	49.6	52.2					
45	2,253	2,250	51.9	52.2	50.8	53.4					
46	2,303	2,300	53.0	53.3	52.0	54.4					
47	2,353	2,350	54.2	54.4	53.0	55.4					
48	2,403	2,400	55.3	55.5	54.1	56.4					
49	2,453	2,450	56.3	56.5	55.1	57.3					
50	2,503	2,500	57.6	57.8	56.3	58.4					
51	2,553	2,550	58.6	58.8	57.3	59.4	¥53,000	¥53,500	TB-24V-090A	TC-24V-100	7
52	2,603	2,600	59.7	59.9	58.4	60.4					
53	2,653	2,650	60.8	61.0	59.4	61.5					
54	2,703	2,700	61.9	62.1	60.4	62.5					
55	2,753	2,750	63.0	63.2	61.5	63.5					
56	2,803	2,800	64.2	64.4	62.6	64.6					
57	2,853	2,850	65.4	65.6	63.7	65.7					
58	2,903	2,900	66.5	66.7	64.8	67.5					
59	2,953	2,950	67.4	67.6	65.6	67.5					
60	3,003	3,000	68.0	68.2	66.3	68.2					

リードタイム目安

2700K・3000K・3500K：14時締切/7営業日後出荷

その他色温度：14時締切/9営業日後出荷

※1700mm以上の長さは、上記納期に加え1営業日いただきます

○8本(12m) / △12本(18m) / □25本(35m) / ■35本(50m)

4	●	14時締、翌4日出荷	月	火	水	木	金
7	○	14時締、翌7営業日に出荷	月	火	水	木	金
9	△	14時締、翌9営業日に出荷	月	火	水	木	金
12	□	14時締、翌12営業日に出荷	月	火	水	木	金
18	■	14時締、翌18営業日に出荷	月	火	水	木	金

注文日

出荷日