

TQDシリーズ電気特性表

基板数	全長 (mm)	100V		200V		希望小売価格		電源型番	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	コード	コネクタ	要信号線	信号線不要
1	68	1.0	3.0	1.2	6.6	¥9,200	¥10,200	TB-24V-030A	TC-24V-020
2	118	1.6	4.1	1.8	7.5				
3	168	2.2	5.2	2.4	8.6				
4	218	3.0	5.4	3.0	10.2				
5	267	3.8	5.5	3.4	10.5				
6	317	4.5	5.6	4.2	11.0				
7	367	5.0	6.1	4.7	11.3				
8	417	5.6	6.7	5.9	11.4				
9	467	6.2	7.2	6.6	11.8				
10	516	6.8	7.7	7.2	12.1	¥10,400	¥11,400		
11	566	7.4	8.3	7.7	12.6				
12	616	7.9	8.8	8.3	13.1				
13	666	8.5	9.3	8.9	13.7				
14	716	9.1	9.9	9.6	14.5				
15	765	9.7	10.4	10.3	15.4				
16	815	10.2	11.0	11.0	16.4				
17	865	10.8	11.5	11.5	16.9				
18	915	11.3	12.0	12.1	17.4				
19	965	11.9	12.5	12.7	17.9	¥11,500	¥12,500		
20	1,014	12.4	13.0	13.2	18.4	¥12,700	¥13,700		
21	1,064	13.2	13.8	13.9	19.1				
22	1,114	13.7	14.3	14.5	19.5	¥13,800	¥14,800		
23	1,164	14.3	14.8	15.1	20.1				
24	1,214	14.9	15.4	15.6	20.5	¥15,000	¥16,000		
25	1,263	15.4	15.9	16.0	20.9				
26	1,313	16.0	16.5	16.7	21.5	¥16,100	¥17,100		
27	1,363	16.5	17.0	17.2	22.0				
28	1,413	17.1	17.6	17.7	22.5	¥17,300	¥18,300		
29	1,463	17.6	18.1	18.2	22.9				
30	1,512	18.2	18.6	18.8	23.4	¥18,400	¥19,400		
31	1,562	18.8	19.2	19.4	23.9				
32	1,612	19.3	19.7	19.9	24.4	¥19,600	¥20,600		
33	1,662	19.8	20.2	20.4	24.9				
34	1,712	20.3	20.7	20.9	25.4	¥20,700	¥21,700		
35	1,761	20.8	21.2	21.4	25.8				
36	1,811	21.4	21.8	22.0	26.4	¥21,900	¥22,900		
37	1,861	21.9	22.3	22.5	26.8				
38	1,911	22.4	22.8	23.0	27.3	¥23,000	¥24,000		
39	1,961	22.9	23.3	23.4	27.7				
40	2,010	23.3	23.7	23.8	28.1	¥24,200	¥25,200		
41	2,060	24.4	24.1	24.5	28.7				
42	2,110	24.5	24.9	25.0	29.1	¥25,300	¥26,300		
43	2,160	25.0	25.3	25.5	29.5				
44	2,210	25.4	25.7	26.0	29.9	¥26,500	¥27,500		
45	2,259	25.9	26.3	26.5	30.4				
46	2,309	26.6	26.9	27.0	30.9	¥27,600	¥28,600		
47	2,359	27.0	27.4	27.5	31.3				
48	2,409	27.5	27.8	28.0	31.8	¥28,800	¥29,800		
49	2,459	27.9	28.3	28.4	32.2				
50	2,508	28.4	28.7	28.9	32.6			TB-24V-060A	TC-24V-060

基板数	全長 (mm)	100V		200V		希望小売価格		電源型番	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	コード	コネクタ	要信号線	信号線不要
51	2,558	29.1	29.4	29.5	33.2	¥29,900	¥30,900	TB-24V-060A	TC-24V-060
52	2,608	29.5	29.8	29.9	33.5				
53	2,658	30.0	30.3	30.3	33.9	¥31,100	¥32,100		
54	2,708	30.4	30.7	30.8	34.4				
55	2,757	30.9	31.1	31.2	34.7	¥32,200	¥33,200		
56	2,807	31.5	31.8	31.9	35.4				
57	2,857	31.9	32.2	32.2	35.7	¥33,400	¥34,400		
58	2,907	32.4	32.6	32.6	36.1				
59	2,957	32.8	33.1	33.1	36.5	¥34,500	¥35,500		
60	3,006	33.3	33.6	33.6	37.0				
61	3,056	33.3	33.5	33.2	36.4	¥35,700	¥36,700		
62	3,106	33.7	33.9	33.5	36.7				
63	3,156	34.0	34.2	33.8	36.9	¥36,800	¥37,800		
64	3,206	34.3	34.5	34.2	37.3				
65	3,255	34.7	34.9	34.5	37.6	¥38,000	¥39,000		
66	3,305	35.3	35.5	35.1	38.1				
67	3,355	35.7	35.9	35.4	38.4	¥39,100	¥40,100		
68	3,405	36.0	36.2	35.8	38.8				
69	3,455	36.3	36.4	36.0	39.0	¥40,300	¥41,300		
70	3,504	36.5	36.7	36.3	39.2				
71	3,554	37.2	37.4	37.0	39.9	¥41,400	¥42,400		
72	3,604	37.5	37.7	37.3	40.2				
73	3,654	37.9	38.0	37.5	40.4	¥42,600	¥43,600		
74	3,704	38.1	38.3	37.7	40.6				
75	3,753	38.3	38.4	38.0	40.9	¥43,700	¥44,700		
76	3,803	39.0	39.2	38.7	41.4				
77	3,853	39.3	39.5	38.9	41.7	¥44,900	¥45,900		
78	3,903	39.5	39.7	39.3	42.0				
79	3,953	39.8	40.0	39.5	42.3	¥46,000	¥47,000		
80	4,002	39.9	40.1	39.9	42.6				
81	4,052	40.9	41.1	40.5	43.2	¥47,200	¥48,200		
82	4,102	41.1	41.3	40.7	43.5				
83	4,152	41.4	41.5	41.1	43.8	¥48,300	¥49,300		
84	4,202	41.4	41.6	41.3	43.9				
85	4,251	41.8	42.0	41.5	44.1	¥49,500	¥50,500		
86	4,301	42.5	42.7	42.0	44.6				
87	4,351	42.8	43.0	42.3	45.0	¥50,600	¥51,600		
88	4,401	43.0	43.2	42.5	45.1				
89	4,451	43.3	43.5	42.9	45.5	¥51,800	¥52,800		
90	4,500	43.6	43.8	43.1	45.6				
91	4,550	44.5	44.6	43.7	46.2	¥52,900	¥53,900		
92	4,600	44.7	44.9	44.1	46.6				
93	4,650	44.9	45.1	44.3	46.8	¥54,100	¥55,100		
94	4,700	45.1	45.2	44.4	46.9				
95	4,749	45.3	45.5	44.6	47.1	¥55,200	¥56,200		
96	4,799	46.0	46.2	45.2	47.6				
97	4,849	46.3	46.4	45.5	47.9	¥56,400	¥57,400		
98	4,899	46.5	46.7	45.7	48.1				
99	4,949	46.8	46.9	45.9	48.3	¥57,500	¥58,500		
100	4,998	46.9	47.0	46.0	48.4				