

モジュール数	全長 (mm)	100V		200V		24V	価格	電源仕様	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	出力電流 (A)		受信信号線	信号線不要
01	64	1.0	3.1	1.2	6.6	0.02	¥13,400		
02	114	1.6	4.1	1.8	7.4	0.04			
03	164	2.2	5.3	2.4	8.5	0.06			
04	214	2.8	5.8	3.7	9.2	0.08			
05	264	3.8	5.9	4.1	9.8	0.10			
06	314	4.3	6.0	4.5	10.8	0.13			
07	364	5.0	6.1	5.0	12.4	0.15			
08	414	5.6	6.6	5.9	12.6	0.17			
09	464	6.2	7.1	6.5	12.7	0.19			
10	514	6.7	7.6	7.1	12.8	0.21			
11	564	7.3	8.1	7.8	12.4	0.23	¥15,100		TC-24V-020
12	614	7.9	8.6	8.4	13.0	0.25			
13	664	8.5	9.2	9.0	13.8	0.27			
14	714	9.0	9.7	9.8	14.8	0.29			
15	764	9.6	10.3	10.4	15.4	0.31			
16	814	10.1	10.8	11.0	16.0	0.33			
17	864	10.7	11.3	11.5	16.4	0.35			
18	914	11.2	11.8	12.1	17.0	0.37			
19	964	11.8	12.4	12.7	17.6	0.39			
20	1014	12.3	12.9	13.2	18.0	0.41			
21	1064	12.9	13.5	13.8	18.6	0.43			
22	1114	13.4	14.0	14.3	19.0	0.45			
23	1164	14.0	14.5	14.8	19.6	0.47			
24	1214	14.5	15.0	15.4	20.0	0.49			
25	1264	15.1	15.6	15.9	20.4	0.51			
26	1314	15.7	16.1	16.5	21.0	0.53			
27	1364	16.3	16.7	17.0	21.4	0.55			
28	1414	16.7	17.1	17.5	22.0	0.57			
29	1464	17.3	17.7	18.0	22.4	0.59	¥25,100		
30	1514	17.8	18.2	18.6	23.0	0.61			
31	1564	18.4	18.8	19.1	23.4	0.63			
32	1614	18.9	19.3	19.6	24.0	0.65			
33	1664	19.4	19.8	20.1	24.4	0.66			
34	1714	19.9	20.3	20.2	24.8	0.68			
35	1764	20.5	20.8	21.2	25.4	0.70			
36	1814	20.9	21.3	21.7	25.8	0.72			
37	1864	21.5	21.8	22.2	26.2	0.74			
38	1914	22.0	22.3	22.7	26.8	0.76			
39	1964	22.5	22.8	23.2	27.2	0.77			
40	2014	23.0	23.3	23.8	27.6	0.79			
41	2064	23.5	23.8	24.2	28.2	0.81			
42	2114	24.0	24.3	24.8	28.6	0.83			
43	2164	24.5	24.8	25.3	29.0	0.85			
44	2214	24.9	25.2	25.8	29.6	0.86			
45	2264	25.5	25.8	26.2	30.0	0.88			
46	2314	25.9	26.2	26.8	30.4	0.90			
47	2364	26.5	26.7	27.2	30.8	0.91	¥40,100		TC-24V-060
48	2414	26.9	27.1	27.7	31.2	0.93			
49	2464	27.4	27.6	28.1	31.6	0.95			
50	2514	27.8	28.1	28.6	32.0	0.96			
51	2564	28.4	28.6	29.0	32.6	1.02			
52	2614	28.8	29.0	29.5	32.8	1.04			
53	2664	29.3	29.5	29.9	33.2	1.05			
54	2714	29.7	29.9	30.4	33.6	1.07			
55	2764	30.2	30.4	30.8	34.2	1.09			
56	2814	30.6	30.8	31.3	34.6	1.10			
57	2864	31.1	31.3	31.7	35.0	1.12			
58	2914	31.5	31.7	32.1	35.4	1.13			
59	2964	32.0	32.2	32.8	35.6	1.15			
60	3014	33.4	33.6	33.2	36.2	1.17			
61	3064	33.8	34.0	33.5	36.6	1.18			
62	3114	34.2	34.4	33.9	36.8	1.20			
63	3164	34.6	34.8	34.3	37.2	1.21			
64	3214	35.0	35.2	34.7	37.6	1.23			
65	3264	35.4	35.6	35.1	38.0	1.24	¥55,100		

モジュール数	全長 (mm)	100V		200V		24V	価格	電源仕様	
		消費電力 (W)	皮相電力 (VA)	消費電力 (W)	皮相電力 (VA)	出力電流 (A)		受信号線	伝号線不要
66	3314	35.8	36.0	35.4	36.2	1.26	¥55,100	TB-24V-060A	TC-24V-060
67	3364	36.2	36.3	35.8	36.6	1.27			
68	3414	36.6	36.7	36.1	39.0	1.29			
69	3464	36.9	37.1	36.5	39.2	1.30			
70	3514	37.3	37.5	36.9	39.6	1.32			
71	3564	37.7	37.8	37.2	40.0	1.33			
72	3614	38.1	38.2	37.6	40.2	1.35			
73	3664	38.4	38.6	37.9	40.6	1.36			
74	3714	38.8	39.0	38.2	40.8	1.38			
75	3764	39.1	39.3	38.6	41.2	1.39			
76	3814	39.5	39.7	38.9	41.6	1.40			
77	3864	39.8	40.0	39.2	41.8	1.42			
78	3914	40.2	40.4	39.6	42.2	1.43			
79	3964	40.6	40.7	39.9	42.4	1.45			
80	4014	40.9	41.0	40.2	42.8	1.46			
81	4064	41.2	41.4	40.5	43.0	1.49			
82	4114	41.6	41.7	40.9	43.4	1.50			
83	4164	41.9	42.0	41.2	43.6	1.52			
84	4214	42.2	42.4	41.5	44.0	1.53			
85	4264	42.6	42.7	41.8	44.2	1.54			
86	4314	42.8	43.0	42.1	44.6	1.56			
87	4364	43.2	43.3	42.4	44.8	1.57			
88	4414	43.5	43.6	42.7	45.0	1.58			
89	4464	43.9	44.0	43.0	45.4	1.60			
90	4514	44.1	44.3	43.3	45.6	1.61			
91	4564	44.4	44.6	43.6	46.0	1.63			
92	4614	44.7	44.9	43.9	46.2	1.64			
93	4664	45.1	45.2	44.2	46.4	1.65			
94	4714	45.4	45.5	44.4	46.8	1.67			
95	4764	45.7	46.0	44.7	47.0	1.68			
96	4814	46.0	46.3	45.0	47.4	1.69			
97	4864	46.3	46.5	45.3	47.6	1.70			
98	4914	46.5	46.7	45.5	47.8	1.72			
99	4964	46.9	47.2	45.8	48.0	1.73			
100	5014	47.5	47.6	46.1	48.4	1.74			
101	5064	48.3	48.5	47.2	49.8	1.75			
102	5114	48.6	48.9	47.5	50.1	1.76			
103	5164	48.9	49.1	47.8	50.4	1.77			
104	5214	49.2	49.4	48.1	50.6	1.78			
105	5264	49.5	49.7	48.6	50.9	1.79			
106	5314	49.8	50.0	48.9	51.1	1.80			
107	5364	50.1	50.3	49.2	51.4	1.81			
108	5414	50.3	50.5	49.4	51.7	1.82			
109	5464	50.5	50.7	49.7	51.9	1.83			
110	5514	50.9	51.1	50.0	52.1	1.84			
111	5564	51.1	51.3	50.2	52.4	1.85			
112	5614	51.4	51.6	50.4	52.6	1.86			
113	5664	51.7	51.8	50.7	52.8	1.87			
114	5714	52.0	52.2	51.0	53.2	1.88			
115	5764	52.2	52.4	51.2	53.3	1.89			
116	5814	52.4	52.6	51.4	53.5	1.90			
117	5864	52.6	52.9	51.7	53.7	1.91			
118	5914	52.9	53.1	51.9	54.0	1.91			
119	5964	53.2	53.4	52.1	54.2	1.92			
120	6014	53.4	53.6	52.4	54.5	1.93			
121	6064	53.7	53.9	52.6	55.0	1.94			
122	6114	53.9	54.1	52.8	54.8	1.95			
123	6164	54.0	54.3	53.0	55.0	1.96			
124	6214	54.2	54.4	53.1	55.2	1.97			
125	6264	54.5	54.7	53.4	55.4	1.98			
126	6314	54.7	54.9	53.6	55.7	1.99			
127	6364	55.1	55.3	53.8	55.8	2.00			
128	6414	55.4	55.6	54.2	56.2	2.00			
129	6464	55.8	56.0	54.2	56.2	2.01			
130	6514	56.1	56.3	54.6	56.6	2.02			